

sottovaso • saucer | style collection



LLDPE	100% recyclable	lightweight	antishock	U.V. resistant	-65° C + 85° C resistant

I valori riportati si riferiscono a quanto specificato nella scheda tecnica del produttore delle materie prime
The values shown refer to the specifications in the technical sheet of the raw materials producer



art.	size	C	F	G	N	O	P		
2135	Ø 22	3,4	22,0	22,0	17,5	15,0	2,6	1	45
2136	Ø 25	3,6	25,0	25,0	21,0	18,0	3,0	1	45
2137	Ø 28	4,0	28,0	28,3	23,8	20,6	3,2	1	45
1546	Ø 30	5,0	30,0	30,0	25,7	21,4	3,8	1	45
1547	Ø 32	5,0	32,0	32,0	27,8	23,4	3,8	1	45
2138	Ø 33	4,2	33,0	32,8	28,5	25,7	3,5	1	45
1548	Ø 36	5,0	36,0	36,0	32,0	27,5	3,7	1	45
1549	Ø 41	5,0	41,0	41,0	37,0	30,0	4,3	1	45
2293	Ø 44	5,2	44,0	44,0	40,0	32,3	4,3	1	45
1550	Ø 47	5,5	47,0	48,0	43,5	37,0	4,7	1	45
2312	Ø 50	5,6	50,0	50,3	46,5	40,0	4,9	1	45
1551	Ø 53	5,5	53,0	53,2	49,3	42,0	5,0	1	45
1552	Ø 56	6,0	56,0	57,3	52,3	46,0	5,0	1	45
1553	Ø 63	7,0	63,0	64,0	59,0	51,0	5,8	1	45
2313	Ø 70	7,1	70,0	70,5	67,0	58,5	6,2	1	45
1587	Ø 77	7,5	77,0	76,5	72,0	63,5	6,3	1	45

Le misure sono espresse in centimetri
Measures are understood in centimeters

colori • colors

45 terra di siena

simbologia • symbols



euro3plast spa

viale del lavoro, 45
36048 ponte di barbarano (vi) • italy
tel +39 0444 788200 • fax +39 0444 788290

r.e.a. VI n. 125725
cap.soc € 3.000.000 int. vers.
pi/cf/vat (IT) 00331710244

www.euro3plast.com
info@euro3plast.com